

# SPECIFICATION & PROCEDURAL DATA SHEET

## ORGANOIL - DECKING OIL/ EXTERIOR OIL

### *CLASSIC CLEAR - JARRAH – UV/ RED - MERBAU*

**DESCRIPTION:** For the nourishment and protection of all external exposed timbers. Tung and other vital plant oils/extracts have been impregnated with refined bees wax and U-V ray absorbing oxides & UV rated colour enhancers, guarding against exposure degradation and wood-rot.

**USES:** Exterior timber **Decking, Joists/Bearers, Cladding, Railings/Posts, Fencing and BBQ Trolleys.**  
This product is not suitable for use on tongue and groove verandah flooring or internal floors.

**SPECIAL NOTES:**

- New Decking** – greater quantities of hardwoods (particularly Spotted Gum and plantation species) are arriving at construction site precariously high in moisture content. Enquire as to the grade/s and moisture levels of your supply, the use of Woodguard is recommended for timbers of this nature. **Refer can instructions for preparation & application**
- Joists/ Bearers** – if accessible, or prior to installation, oil-seal these supportive structures (and underside of decking slats) with one, liberal application. Woodguard could be used instead.
- Previously Finished timbers** – given the predominant use of synthetic resins in most other-brand acrylics, emulsions and oils, ORGANOIL products may not compatible with them. If wishing to change to our products, you should thoroughly wash, then sand down surfaces prior to using this product. (Refer: Timber Preparation sheet)
- Areas under cover will not require recoating as often as fully exposed timbers.**

**APPEARANCE:** **MATT** results only. On timbers i.e. Teak, Cyprus, Batu, Treated Pine & other timbers. On timbers i.e. Merbau, Kwila, Jarrah, Redgum, Tallowood, Cedar & other timbers with a pink-red undertone use **U/V RED OR MERBAU** to enhance the natural colour (may be also used on treated pine for a light reddish hue). **CLASSIC CLEAR** should be used if seeking a neutral/ natural effect (i.e. the colour of any timber when wetted). However CLASSIC CLEAR will not give the longevity of colour achieved with **RED HIGHLIGHTER and MERBAU, ALL OF THE ABOVE will certainly out perform products containing Petroleum Liquid Hydrocarbons i.e. Kerosene.**  
**JARRAH** contains a heavy weight of pigment & will result in a solid cover look it is only suited to Treated Pine & **“OLD”** weathered Hardwoods.

**SIZES AVAILABLE:** **1 ltr, 4 ltr & 10 ltr cans.** For availability visit website home page.

<b>COVERAGE:</b>	(Approximately)	<b>1<sup>st</sup> Coat</b>	<b>2<sup>nd</sup> Coat/Re-coat</b>
	<b>SOFTWOODS</b> (treated pine etc)	<b>4-6 sq. metres/litre</b>	<b>6-8 sq. metres/litre</b>
	<b>HARDWOODS</b> (incl. cypress)	<b>7-10 sq. metres/litre</b>	<b>10-14 sq. metres/litre</b>

**PREPARATION:**

- 1 Remove all sawdust, nails, metal filings, sand, cement dust etc. from on or near timber surfaces prior to (and after) application of DECKING/ EXTERIOR OIL. Such materials contain elements that can markedly stain should any moisture react with them!**
- 2 Ensure timber is clean (washed) and dry (min. 48 hrs since last wetted). If rain is imminent delay job. (Refer: Timber Preparation sheet)**

**APPLICATION:**

- 1. Stir well prior and during use. This maintains even distribution of ingredients throughout.**
- 2. Apply with brush or lambswool applicator. We do not recommend rollers (unless you can lock the rolling mechanism) as they “splash” too much oil around.**
- 3. Apply **2** coats (1 only when rejuvenating) a minimum 24 hours apart.**
- 4. It is essential that within 1-2 hours of each application (and when re-coating) you dry-brush or cloth in excess surface oil. **NOTE: DO NOT overapply oil. Building oil finishes above the timber's surface does not achieve greater protection; it only results in tackiness, dirt/dust collection and ready marking of surface.****

**CLEAN UP:** Hot soapy water or Gum Turpentine. Oil splatters/spillage should be wiped from glass, aluminium, steel, plastic, etc. within 12 hours to avoid permanent marking/staining.

**MAINTENANCE:** The horizontal aspect of decking timbers makes for ready collection of air-borne pollutants (roadway, airway and particularly gum soots). Given your location to such you will need to wash surfaces occasionally and always before re-oiling (see Timber Preparation sheet) After ensuring surfaces are clean (washed) & dry, a further coat should be applied every 6-12 months in fully exposed conditions & /or every 12-24 months if not fully exposed. Only apply to areas seen to be necessary ( **If after washing beading of water on timber occurs oil is still present therefore re-oiling is not yet necessary in these areas.**)

**BOTTOM LINE:** Our belief is that the primary focus should be on preservation against wood degradation and rot. We supply a genuine Decking/ Exterior Oil to fulfill that need, by washing external timber & applying a nourishing (plant) oil your timbers will be protected in the most environmentally & user friendly way.

CONDITIONS: OUR INFORMATION IS GIVEN IN GOOD FAITH AND IS BASED ON RESULTS OBTAINED FROM EXPERIENCE AND TESTS.

MANUFACTURED BY PREP PRODUCTIONS Pty.Ltd.

P.O. BOX 860 SUTHERLAND NSW 1499 AUSTRALIA ph; 1300 799 432 FAX: (02) 8569 2368

Email: sales@prep-productions.com Website: www.prep-productions.com