

SPECIFICATION & PROCEDURAL DATA SHEET

ORGANOIL - *Olde Style* DANISH OIL

- DESCRIPTION:** Designed to highlight and finish timber with a warm colour/character enhancement and attainment of traditional patina results. A pure, natural plant oil product formulated to better reflect the original, heavy-oil mixes that gave "Danish Oil" its renown. Will not go off in can after opening (shelf-life several years) providing foreign matter is not introduced into the oil. Once dry, is both FOOD and CHILD-SAFE.
- USES:** Internal (only) woodworking, furniture, joinery and other non-traffic feature timbers such as wall/ceiling panelling and exposed beams. NOT for FLOORING or BENCHTOP use.
- SPECIAL NOTES:**
- Prior to choosing/use refer to KEY CONSIDERATIONS at icon on home page (website).
 - This product is not fully ingredient-considerate of wet-areas (bathroom/laundry etc.) ORGANOIL GARDEN FURNITURE OIL, with its anti-fungal oils and bees wax additives, would best address timbers in these locations. Though conduct Danish Oil **PREPARATION/APPLICATION** procedures (given below) for best finishing results.
 - With **ply-wood** projects, you are unlikely to achieve quality finishing unless you conduct the final wax polishing advocated (**1 coat oil**, left to dry, light sand, then **1 or 2** applications of wax as instructed).
- APPEARANCE:** Will result in a clear, light wet-look. As an indication, lightly dampen raw wood with water to appreciate oil's propensity to amplify the inherent colours and wood-grain.
- PATINA/SHINE:** With modest preparation and application effort you only achieve a modest, MATT finish. Should you conduct finer preparatory sanding and advised friction-on-application/buffing procedure, high SATIN results are achievable.
- STAINING:** This product is a penetrative, clear oil finish and should NOT have other-brand pigments/colourants added to it.
- SIZES AVAILABLE:** **500ml, 1 ltr, 4 ltr & 10 ltr cans.** For availability visit website home page.
- | | | |
|------------------|-------------------------------|------------------------------------|
| COVERAGE: | 1st Coat | 2nd Coat/Re-coat |
| Softwoods | 5-9 sq. metres/litre | 8-12 sq. metres/litre |
| Hardwoods | 10-14 sq. metres/litre | 18-20 sq. metres/litre |
- (lower parameters of coverage are for rough-sawn/higher parameters for dressed)*
- PREPARATION:**
- For best quality results on furniture/joinery, further dry-sand through the grits to **600-1200 (the finer the better!)**. Commencing grits are relevant to original surface supplied.
 - Ensure timber surfaces are clean and dry – remove sawdust, metal filings etc. from on or near the timber prior to oiling.
 - If access to rear/underside surfaces are available prior to (or after) installation, apply **1** coat to such areas to facilitate all-round moisture protection (preparatory sanding of such areas is not necessary).
- APPLICATION:**
- Ensure you have read & understood aforementioned **usage, notes** and **preparation** advice first. **If skin-sensitive wear oil-impervious gloves.** Ensure good ventilation.
 - Apply with brush or lambswool applicator **2 (two)** coats only, & **24** hours apart, (**1** only when rejuvenating existing oiled timber). **Special note: It would also only be 1 (one) application of oil should you be intending to conduct a Wax-Polishing final finish.**
 - (OPTIONAL) For higher patina: with each application, and prior to next step **4**, friction-rub oiled surfaces with white, synthetic pad/s .
 - It is **ESSENTIAL** that within $\frac{1}{2}$ to **1** hour of **EACH** application (and when rejuvenating) you firmly dry-cloth off excess oil/residues to ensure a non-tacky, non dust-collecting surface!
 - Power buffing with lambswool pad (a further **24-48** hrs after last oiling) would again contribute to patina.
 - Now leave finished project to fully cure/air-dry for **5-7** days (avoiding spills or use).
- CLEAN UP:** Hot soapy water or Gum Turpentine.
- MAINTENANCE:** To clean your oiled timber, or prior to re-application, wipe over surfaces with solution of warm water and methylated spirits – use with synthetic scourer for difficult to remove grime. Re-oil (**ONE** coat) as necessary. **If having wax finished do NOT oil again, wax only.**
- WAXING:** Should you be seeking the pale satin and tactile response that wax finishes deliver, we recommend the use of ORGANOIL'S *Natural Wax & Polish* (as instructed), though allow minimum **14** days curing/drying period of oil application to elapse. *Olde Style* DANISH OIL when used as directed will result in a finish with a warm patina and quality, long-lasting results.
- Finally, always refer to can's instruction label for other storage, disposal, health and safety notes.**

